

RECEIVED  
CENTRAL FAX CENTER

JUN 08 2007

IN THE CLAIMS:

1. (Currently Amended) An injector system comprising an injector and a syringe,  
the injector system comprising:  
a syringe comprising:  
a body comprising a forward end and a rearward end; and  
a plunger movably disposed in the body; and  
an injector comprising:  
a housing; and  
a piston movably disposed at least partially within the housing and  
operable to drive the plunger of the syringe in a forward direction without a  
connective engagement between the piston and the plunger to dispense fluid  
from the forward end of the body during an injection procedure, wherein the  
piston comprises an elastomeric member adapted to expand in a radial direction  
to connectively engage the plunger to retract the plunger within the syringe.
2. (Canceled)
3. (Canceled)
4. (Canceled)
5. (Canceled)
6. (Original) The injector system of claim 1 wherein the piston is adapted to  
engage the plunger without regard to the orientation of the plunger with respect to the  
piston.

7. (Original) The injector system of claim 1 wherein the piston is adapted to drive the plunger without regard to the orientation of the plunger with respect to the piston.

8. (Currently Amended) An injector system comprising an injector and a syringe, the injector system comprising:

a syringe comprising:

a body comprising a forward end and a rearward end; and

a plunger movably disposed in the body; and

an injector comprising:

a housing; and

a piston movably disposed at least partially within the housing and operable to drive the plunger of the syringe in a forward direction without a connective engagement between the piston and the plunger to dispense fluid from the forward end of the body during an injection procedure, wherein the piston is adapted to connectively engage the plunger to retract the plunger within the syringe,

wherein the piston comprises a collet member comprising one or more segment members adapted to deflect inside the plunger in a radial direction to engage the plunger when the piston is retracted.

9. (Previously Presented) The injector system of claim 8 wherein the piston is adapted to engage the plunger without regard to the orientation of the plunger with respect to the piston.

10. (Previously Presented) The injector system of claim 8 wherein the piston is adapted to drive the plunger without regard to the orientation of the plunger with respect to the piston.

11. (Previously Presented) An injector system comprising an injector and a syringe, the injector system comprising:

a syringe comprising:

a body comprising a forward end and a rearward end; and

a plunger movably disposed in the body; and

an injector comprising:

a housing;

a piston movably disposed at least partially within the housing and operable to drive the plunger of the syringe in a forward direction without a connective engagement between the piston and the plunger to dispense fluid from the forward end of the body during an injection procedure, wherein the piston is adapted to connectively engage the plunger to retract the plunger within the syringe;

a sleeve member associated with the piston; and

one or more plunger gripper members associated with the piston and adapted to be biased by the sleeve member into engagement with the plunger upon retraction of the piston.

12. (Previously Presented) The injector system of claim 11, further comprising:

a collar connected to one end of the piston sleeve, the collar defining an opening through which the piston extends;

a plunger cap connected to the collar, the plunger cap defining an interior space and a plurality of slots formed in a side thereof;

a gripper extender disposed on an end of the piston within the interior space of the plunger cap;

a plurality of grippers disposed through the slots and engageable with the gripper

extender; and

a biasing member in contact with the piston sleeve;

whereby, upon movement of the piston in a rearward direction, the biasing member biases movement of the piston sleeve to substantially prevent movement of the piston sleeve in the rearward direction to cause the gripper extender to push the plurality of grippers through the slots in the plunger cap into engagement with the plunger within the syringe.

13. (Previously Presented) The injector system of claim 11 wherein the piston is adapted to engage the plunger without regard to the orientation of the plunger with respect to the piston.

14. (Previously Presented) The injector system of claim 11 wherein the piston is adapted to drive the plunger without regard to the orientation of the plunger with respect to the piston.

15. (Currently Amended) The injector system of claim 8 further including a rod member driven through the center of the collect mechanism, wherein the rod member [control] controls the one or more segmented members.